

SAFETY DATA SHEET (SDS)

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE SUPPLIER

| | |
|--|--|
| (a) Product Identifier | LSC Wood Filler (Teak/Natural) |
| (b) Other means of identification | Wood Filler. Packaging: PVC Container : 500g / 1.5kg / 5kg / 20kg PVC bottles: ± 2kg, Metal tin: ± 10kg. |
| (c) Recommended use and restrictions on use | Filler for furniture covering grains and holes on wood surfaces |
| (d) Details of the principal supplier | LSC Chemical & Paints Sdn. Bhd, No. 39, Jalan Bestari 2/KU7, Kawasan Perindustrian Kapar Bestari, 42200 Kapar, Selangor, Selangor Darul Ehsan, Malaysia. Tel.: + 603-3292 8816 |
| (e) Email | lsc_cp@hotmail.com |

2. HAZARD IDENTIFICATION

NO CLASSIFIED

3. COMPOSITION AND INFORMATION OF THE INGREDIENTS

| Chemical Name | CAS Number | Conc. |
|-------------------|------------|--------|
| Calcium Carbonate | 1317-65-3 | 65-75% |
| Water | 7732-18-5 | 20-30% |
| Additives | NA | <2% |

4. FIRST AID MEASURES

| (a) Description of first aid measures | |
|--|---|
| Inhalation | In all cases of doubt, or when symptoms persist, seek medical attention Move person to fresh air area. Get medical attention. |
| Eye contact | Avoid contact with direct sunlight or UV-light Irrigate copiously with fresh water for at least 10 minutes (holding eyelids apart). Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention. |
| Skin contact | Remove contaminated clothing Wash skin thoroughly with soap and cold water or use recognized skin cleanser. Avoid contact with direct sunlight or UV-light DO NOT clean the skin with solvent. |
| Ingestion | Get medical attention immediately Do not induce vomiting. |

LSC Chemical & Paints Sdn. Bhd. believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

LSC Chemical & Paints Sdn. Bhd,
No. 39, Jalan Bestari 2/KU7, Kawasan Perindustrian Kapar Bestari, 42200 Kapar, Selangor Darul Ehsan.

5. FIRE-FIGHTING MEASURES

| | |
|---------------------------------|---|
| Classification | Not Combustible |
| *Flash Point | NA |
| *Explosive Limits (% By Volume) | - |
| LEL | NA |
| UEL | NA |
| Fire Extinguishing Media | Foam, CO2, Dry Powder, Sand |
| Fire Fighting Procedures | Respiratory protection is required for fire-fighting personnel. Do not breathe fumes. Stay upwind, if possible. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|--|---|
| (a) Personal precautions, protective equipment and emergency procedures | Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area. Ventilate well. Stop leak if possible without risk. Avoid contact with skin and eyes. Do not breathe vapour. |
| (b) Environmental precautions | Avoid discharge into lakes, ponds, streams, or public waters. |
| (c) Methods and material for containment and cleaning. | Confine and absorb with sand, earth or other non-combustible material; place material into approved containers for disposal |

7. HANDLING AND STORAGE

| | |
|--|---|
| (a) Precautions for safe handling | Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Do not keep product for a long time (> 2years). Keep good house-keeping. |
| (b) Conditions for safe storage, including any incompatibilities. | CAUTION - FLAMMABLE - keeps away from all sources of ignition. "Empty" containers may contain residue, which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use non-sparking tools when opening and closing containers. Maintain well-ventilated work areas to minimize exposure when handling this material. |

8. EXPOSURE CONTROL/PERSONAL PROTECTION

| | |
|-------------------------------|---|
| Respiratory Protection | Use approved respiratory protection such as air supplied mask if used in enclosed spaces. |
| Ventilation | Sufficient ventilation should be provided during application |
| Protective Gloves | Chemically resistant gloves |
| Eye Protection | Chemical splash-proof goggles or face shield |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------------|-------------|
| Physical state | Brown Paste |
| Flash Point | >68% |
| Viscosity (at 30°C) | Paste |
| Specific gravity | - |

LSC Chemical & Paints Sdn. Bhd. believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

LSC Chemical & Paints Sdn. Bhd,
 No. 39, Jalan Bestari 2/KU7, Kawasan Perindustrian Kapar Bestari, 42200 Kapar, Selangor Darul Ehsan.

| | |
|---------------------|----------|
| Solubility in water | Miscible |
| pH value | 7.8-8.5 |

10. STABILITY AND REACTIVITY

| | |
|--------------------------------------|--|
| Conditions To Avoid | Heat, spark, open flame and static charge build-up |
| Incompatibility (Materials to avoid) | Strong oxidizing agents |
| Decomposition Products | Carbon monoxide and carbon dioxide |

11. TOXICOLOGY INFORMATION

There are no data available on the preparation itself. Repeated or prolonged contact with the skin may cause removal of natural fat from the skin resulting in non-allergic dermatitis and absorption through the skin.

12. ECOLOGICAL INFORMATION

No ecological studies have been carried out on this product.

13. DISPOSAL CONSIDERATIONS

If possible, recover the product, otherwise dispose by incinerate or land fill must be in compliance with all local laws and regulation.

14. TRANSPORT INFORMATION

The product is considered as a "Non-Dangerous Product"

15. REGULATORY INFORMATION

Regulatory information in country or region with regards to this product should be observed.

16. OTHER INFORMATION

It is advisable to read the respective R-phrases and S-phrases on the labels of the container prior handling the product.

This Material Safety Data Sheet contains information, which is only provided as a guide to the use of this product and is correct to the best of our knowledge.

KTH Paint Industries Sdn Bhd cannot offer any guarantee as to its accuracy or exhaustiveness. All chemicals may present unforeseen risks and should be used with care.

Further, we cannot guarantee that the risks referred to the above are the only risk present.