



TECHNICAL DATA SHEET (TDS) LSC HIGH GLOSS PAINT

Product Description

LSC High Gloss PAINT is a single component solvent-based alkyd enamel. It is having fast drying time, yet still gives very high gloss finishing to painted surfaces. It is suitable for interior and exterior use. For better long-lasting exterior use and gloss retention, this product should be over coated with Alkyd Finish.

Uses

As intermediate coat or top-coat in a multi-coat coating system. Most suitable for use on steel, GI and others surfaces. Main for indoor structure and general industrial steel painting.

Composition

Pigment : Various pigments.
Binder : Modified alkyd
resin Solvent : Hydrocarbon

Physical Characteristics of the Paint:

Density : 0.92– 1.15 (depending on colors).
Volume Solid : 52 ± 5%
Viscosity : 70 ± 2 KU at 30°C
Theoretical Coverage : 11.5 – 15 m²/liter
Color : Wide range of colors.

Coating Properties:

Recommended Dry Film Thickness	: 35-45 microns per coat
Recommended Wet Film Thickness	: 67 - 87 microns per coat
Recommended Numbers of coat	: One to two
Drying Time	: Touch Dry: 20 mins Hard Dry: 4 to 6 hours
Recoating interval	: At least 8 hours
Curing Time	: 1 day

Surface Preparation:

Previous painted surface and bare substrate must be completely dry and free from rust, mill-scale, dirt, grease and other contaminants before painting. For maximum adhesion and durability of paint performance, all bare surfaces should be prepared by means of sand paper, hand tools, power tools and etc.

Application Method:

Method of Application	: Brush, roller, and spray application.
Product Preparation	: Stir mixture thoroughly before use. No thinning is required rolling and brushing. However, 10 – 30 % of thinner may be added for spraying application.
Pot Life (at 30oC)	: No pot life limit

Safety Precaution:

1. This product is flammable. Keep away from sources of ignition.
2. Keep container tightly closed and keep out of reach of children.
3. Wear suitable personal protective clothing during painting.
4. Ensure adequate ventilation. Do not breathe or inhale spray mist.
5. Do not apply when the relative humidity exceeds 85%.
6. Avoid skin and eye contact. Spillage on skin should be removed immediately with cleanser, soap and water. Eye should be well flushed with water and seek medical advice immediately if discomfort persists.